NASA/TM-2002-211720



A Parametric Assessment of the Mission Applicability of Thin-Film Solar Arrays

David J. Hoffman Glenn Research Center, Cleveland, Ohio Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the Lead Center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peerreviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- TECHNICAL MEMORANDUM. Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.

- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- TECHNICAL TRANSLATION. Englishlanguage translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized data bases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at http://www.sti.nasa.gov
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at 301–621–0134
- Telephone the NASA Access Help Desk at 301–621–0390
- Write to: NASA Access Help Desk NASA Center for AeroSpace Information 7121 Standard Drive Hanover, MD 21076

NASA/TM-2002-211720



A Parametric Assessment of the Mission Applicability of Thin-Film Solar Arrays

David J. Hoffman Glenn Research Center, Cleveland, Ohio

Prepared for the Space Power Workshop 2002 cosponsored by the Air Force Research Laboratory, USAF Space and Missile Systems Center, and the Aerospace Corporation Redondo Beach, California, April 22–25, 2002

National Aeronautics and Space Administration

Glenn Research Center

This report contains preliminary findings, subject to revision as analysis proceeds.

Available from

NASA Center for Aerospace Information 7121 Standard Drive Hanover, MD 21076 National Technical Information Service 5285 Port Royal Road Springfield, VA 22100

A Parametric Assessment of the Mission Applicability of Thin-Film Solar Arrays


David J. Hoffman National Aeronautics and Space Administration Glenn Research Center Cleveland, Ohio 44135

Summary

Results are presented from a parametric assessment of the applicability and spacecraft-level impacts of very lightweight thin-film solar arrays with relatively large deployed areas for representative space missions. The most and least attractive features of thin-film solar arrays are briefly discussed. A calculation is then presented illustrating that from a solar array alone mass perspective, larger arrays with less efficient but lighter thin-film solar cells can weigh less than smaller arrays with more efficient but heavier crystalline cells. However, a spacecraft-level systems assessment must take into account the additional mass associated with solar array deployed area: the propellant needed to desaturate the momentum accumulated from area-related disturbance torques and to perform aerodynamic drag makeup reboost. The results for such an assessment are presented for a representative low Earth orbit (LEO) mission, as a function of altitude and mission life, and a geostationary Earth orbit (GEO) mission. Discussion of the results includes a list of specific mission types most likely to benefit from using thin-film arrays. The presentation concludes with a list of issues to be addressed prior to use of thin-film solar arrays in space and the observation that with their unique characteristics, very lightweight arrays using efficient, thin-film cells on flexible substrates may become the best array option for a subset of Earth orbiting and deep space missions.

Photovoltaic Array Metrics Which array technology will have the advantage? Feature Low Cost Low Mass penalty array - propellant) for lower altitude. Eo • Packageabiliy · Deployabiliy Crystalline-cell arrays. Highest Specific Area (W/m²) Small Deployed Area - Reliable Performance Constabline-cell arrays for the story of succession performance, but thin-film arrays show promise. Radiation

Thin-film cells easier to isolate from plasma



Op. Temperature

Hi-Voltage Capability

How efficient do thin-film cells have to be?

Arrays with <u>less efficient but lighter</u> thin-film cells can match the mass of arrays with <u>more efficient but heavier</u> MBG crystalline cells.

1st Order: Equate array specific power at BOL, 28° C W/kg=(W/m²) / (kg/m²)

=>TF Cell Eff = MBG Cell Eff x (<u>Array Structure + TF Cell Area Sp. Mass</u>) (Array Structure + MBG Cell Area Sp. Mass)

- Mass-Equivalent array with a 0.5 kg/m² structure.
 - 30% efficient 1.0 kg/m² MBG cells
 - 4% efficient 0.2 kg/m² thin-film cells


24.07091


Support structure will be optimized for lightweight thin-film cell blankets


 12% TF cells on 0.27 kg/m² structure matches the specific mass of 30% MBG cells on 0.5 kg/m² structure for arrays with same deployed stiffness.


However, to meet EOL power rqmt at max op temp

Need 17% BOL 28°C Thin-Film cells










NASA/AFRL Sponsored Comprehensive Solar Array Study by AEC Able

- Missions
- LEO, MEO, GEO, SEP Transfer, Interplanetary
- A PARALLE CONTROL OFFICE
- M.C. Crystalling at 25% (30% & 35% Eff.
- •Thin-Film at 10%, 15% & 20% Eff.; 0.2 and 0.4 kg/m²
- Array Technologies
- Rigid Panel, CellSaver, Stretched Lens Array, Aurora, Ultraflex, SquareRigger
- Evaluation of complete systems inclination in the launch restraints, yokes, wire harnesses, deployment synchronization etc.
- Deployed & Stowed Stiffness
- Cell operating temperature
- Radiation degradation




Preliminary Array Study Results

Performance of Shielded Thin-Film & 3J Crystalline PV in Various Earth Orbits

- Assumed photovoltaic only mass:
- CICS=02 kg/m (On 30 un tranium foi)
- CainP/GaAs/Ge = 0.75 kg/m² (140 µm thick Ge wafer)
- Radiation shielding optimizes array specific power (W/kg)

Results do not include array structural support mass!

- EOL W/m² always higher for 3J cell compared to CIGS
- EOL Areal Power With Shielding Optimized for W/kg 350.0 **⊠** 30% 3J 300.0 **⊠** 15% CIGS 250.0 2.3x 2.2x 192.5 200.0 143.0 150.0 4.1x 100.0 46.4 50.0 LEO (1000 km, i = 90°) MEO (8000 km, i = 0 GEO (35,793 km, i = 0°)
- EOL Wikg for shielded cell higher for CIGS except in MEO
- Due to on-negligible shielding and lower areal power density



Solar Array Specific Power

What's in the numerator & denominator?

Mass Specific Power	B01		E91	
Wike	1.43	AL	1 At	1 AU
	28 0	Op. Temp		
10.00				
			149	


Lunar L1 "Gateway" SEP Stage

Features

- 180-esy (ripolinge, 400 km/23/55 til #04tionship.)
- 46-day return, Lunar L1 400 km 28.5° LEO
- 584 KW SEP Stage Power (2 round trips)
- 7,300 m² High-Voltage Thin-Film Solar Arrays (2 wings)
- 12 Direct-Drive Hall Effect 50 kW Engines (incl. 1 spare)


Massidialelelelisies

- 15.0 MT SEP Stage Dry Mass (w/ 20% margin)
- 20.0 MT Xenon propellant
- 600 MT Pavioad
- 65.0 MT Vehicle Initial Mass LEO



Far Term Thin-Film Application Humans on Mars

- 1100-Day Surface Mission
 - Operate ISRU Plant (400-days)
 - Support Crew (500-days)
- 5000-m2, 100 kW Class Array
- Auto-Beolev Ten Signatives
- 4.5-m Reight by 100-m Length
- Thin Film PV on Thin Polymer Membrane Enabling
 - Small Packaging Volume
 - Low Mass



Thin-Film Array Mission Applicability Summary

- Once designed, tested and space-qualified, very lightweight solar arrays using moderate to relatively high efficiency thin-film cells on lightweight flexible substrates will offer significant mass and cost benefits.
- > 10% to 15% (1-Sun AM0) efficient >10-cm² thin-film cells with on low-mass substrates (1-mil metallic, 5-mil pre-preg composite ply, 2-mil polymer, openweave polymer) resulting in solar cell "blankets" at 0.2 to 0.3 kg/m².
- Attractive Earth-Orbiting applications for Thin-Film arrays include:
 - · LEO missions above 500 km to 800 km but below 4,000 km
 - · LEO missions of short duration at lower altitudes
 - · LEO sun-sync missions with array normal perpendicular to velocity vector
 - · LEO-to-GEO transfers
 - GEO missions
 - · Certain very small micro/nanosat missions
- Beyond Earth orbit applications include:
 - LEO-to-L1 SEP Transfers
 - LEO-to-? SEP Transfers
 - Large Surface Power Systems

REPORT DOCUMENTATION PAGE Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services. Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0148), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE		AND DATES COVERED		
	August 2002	Te		Memorandum	
4. TITLE AND SUBTITLE			5. FUNDI	NG NUMBERS	
A Parametric Assessment of	the Mission Applicability of Th	nin-Film Solar Arrays	33 77 T	755 14 16 00	
6. AUTHOR(S)			WU-755-1A-16-00		
David J. Hoffman					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)			9	DRMING ORGANIZATION	
National Aeronautics and Space Administration				RT NUMBER	
John H. Glenn Research Center at Lewis Field				3471	
Cleveland, Ohio 44135–3191					
9. SPONSORING/MONITORING AGEN		ISORING/MONITORING NCY REPORT NUMBER			
National Aeronautics and Space Administration					
Washington, DC 20546-00	NAS	SA TM—2002-211720			
11. SUPPLEMENTARY NOTES					
person, David J. Hoffman, or	the Aerospace Corporation, Rerganization code 6920, 216–433				
12a. DISTRIBUTION/AVAILABILITY STATEMENT				12b. DISTRIBUTION CODE	
Unclassified - Unlimited Subject Categories: 18 and 2					
Available electronically at http://gltrs.grc.nasa.gov					
This publication is available from the NASA Center for AeroSpace Information, 301–621–0390.					
13. ABSTRACT (Maximum 200 words		14 1 174			
thin-film solar arrays with refeatures of thin-film solar arral alone mass perspective, large with more efficient but heaving additional mass associated with from area-related disturbance ment are presented for a reprince geostationary Earth orbit (Glibbenefit from using thin-film solar arrays in space and the film cells on flexible substrational substrates are presented for the solar arrays in space and the film cells on flexible substrates.	a parametric assessment of the a elatively large deployed areas for any are briefly discussed. A caller arrays with less efficient but lier crystalline cells. However, a with solar array deployed area: the torques and to perform aerody resentative low Earth orbit (LECEO) mission. Discussion of the arrays. The presentation concluses may become the best array of	or representative space reliculation is then present lighter thin-film solar conspace raft-level system the propellant needed to synamic drag makeup relicolor mission, as a function results includes a list of issues que characteristics, very option for a subset of East	nissions. ' ed illustra ells can w as assessn desaturat boost. The n of altitu f specific to be ado lightweig arth orbiti	The most and least attractive ating that from a solar array reigh less than smaller arrays ment must take into account the e the momentum accumulated a results for such an assessde and mission life, and a mission types most likely to dressed prior to use of thin-film ght arrays using efficient, thin-	
Space power; Power generation; Photovoltaics; Solar array; Solar panel				16. PRICE CODE	
17. SECURITY CLASSIFICATION 1 OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICA OF ABSTRACT	ATION	20. LIMITATION OF ABSTRACT	
Unclassified	Unclassified	Unclassified			